



Ready to topcoat, pre-primed timber mouldings for a premium finish

Why EziTrimplus?

With EziTrimplus you can be confident that you have the very best in quality, strength and workability.

- Defect free
- Natural product
- Easy to work with
- Light yet strong and durable
- Pre-primed and ready to top coat

Applications

EziTrimplus mouldings are suitable for any interior finishing application that requires high quality and a great look. EziTrimplus has a wide variety of uses such as **Skirtings, Architraves, Jambs, Reveals, Shelving, Furniture and Bathrooms and Kitchens** (not exposed to constant wetting).

It's a natural product

EziTrimplus is manufactured from sustainable plantation grown Radiata Pine (*Pinus radiata*). Which has been milled, kiln dried and **docked to remove all knots and visible Imperfections**. This is then used to produce a fingerjointed/laminated moulding, or door jamb which has no defects

Storage

Store EziTrimplus in a dry well ventilated area. All possible preventative measures should be undertaken to limit exposure to moisture. Moisture may rise from a substrate below (dirt or concrete) or be atmospheric (rain or humidity). Either may result in EziTrimplus taking in moisture over time.





Innovative Timber Ideas


EziTrimplus

www.ezitrimplus.com

Installation Guide

CUTTING

All EziTrimplus should be cut from the moulded face through to the back face to prevent fibre tear that is inherent with all softwood timber (Picture 1.2).



Correct



Incorrect

CHISELLING & ROUTING

For the ease of chiselling and routing all single rebate Door Jambs have defect free rebates. To ensure the best possible finish we recommend that you only use sharp, well maintained tools.



Correct



Incorrect

NAILING

To achieve the best results from EziTrimplus we recommend using both an adhesive and nails combined.

Hand Nailing

When hand nailing, the use of Bullet Head Brights is recommended (Table 2.1). The hand nailing should be finished with a nail hole punch so the nail sits just below the surface.


EziTrim Thickness	Bullet Head Brights	Paslode TrimMaster	Conventional Airgun
11mm	40mm x 2.0g	38mm	DA38
18mm	50mm x 2.5g	50mm	DA50
30mm	65mm x 2.5g	63mm	DA63

Gun Nailing:


When nailing different mouldings, ensure you adjust the gun with each moulding type to prevent the nail from shooting too deep and to make sure the nail is just below the surface.

When using a nail gun we recommend you use a protective tip to eliminate any bruising that occurs with all softwood products.

As shown below, Paslode Guns use a 'no mar tip'.



Correct



Incorrect

SANDING & PAINTING

Sanding

EziTrimplus requires little or no sanding prior to painting.

Painting

Before painting it is essential to wipe off dust and dirt that may have accumulated on the surface of the moulding. The use of a good quality Acrylic or Enamel paint is recommended for your top Coat. Depending on the desired colour and finish you may need to apply a second coat.

HEALTH & SAFETY

When working with EziTrimplus ensure you use all the correct personal protective equipment: For example mask, gloves, goggles. Machine tools should be fitted with dust extractors and work areas kept clean. Storage and work areas should be adequately ventilated. Machines should be well maintained and the cutting tools should be sharp.

www.ezitrimplus.com